

410-SOLAR-i HANDHELD REFLECTOMETER

Measures total solar reflectance from 335nm to 2500 nm

Designed for increased accuracy when measuring non-uniform or rough materials, the 410-Solar-i retains the original 410-Solar's handheld form factor and in-band spectral resolution. As a result, the 410-Solar-i provides $\pm .02$ measurement accuracy and $\pm .001$ repeatability, a larger beam spot size, and faster measurement and calibration times than the previous 410-Solar model.

BENEFITS

■ 410-Solar upgrades

Faster measure time, larger spot, single cleanable calibration coupon.

■ ASTM compliant

Compliant with ASTM E903, C1549 & E1980.

■ 7 discrete bands

335-380, 400-540, 480-600, 590-720, 700-1100, 1000-1700, 1700-2500.

■ Multiple solar irradiance functions

New or custom functions can be added to the default options including AM 0, 1.5.

■ Cleanable calibration coupon

Calibration coupon can be wiped clean.

■ Immediate data

Touch screen display for data review and management.

APPLICATIONS

■ Cool Building Materials

TSR | SRI | ASTM | LEED | CRRC

■ Space Coatings

Thermal control | α/ϵ | Thermo-optical properties

■ Defense | Aerospace

IR Signature | Low observable paint & coatings

■ Radiative Heat Transfer

Absorptance for thermal modeling

■ LiDAR

Test Target Reflectance




EXAMPLE MENU SCREENS


Measurement screen.



Total solar reflectance calculation for the selected solar irradiance function.



Graphical representation of the measured reflectance values.



ORDERING


Standard components	0410-0015 0410-0001 0410-0107	410-Solar-i Measurement Head Handheld Command Module - 120VAC Glazed Ceramic Calibration Coupon (Non-NIST Traceable)
Options	0410-0002 0410-0123 0410-1016 0410-1009 0410-1019 0410-0207 0410-0200 0410-0019	Benchtop Remote Control Unit - 120VAC Glazed Ceramic Calibration Coupon (NIST Traceable) 410-Series Reflectometer Maintenance and Calibration Plan (Non-NIST) 410-Series Reflectometer Maintenance and Calibration Plan (NIST) 410-Solar-i Extended Warranty SD Card for Extra Data Storage Handheld Command Module - 220VAC Benchtop Remote Control Unit - 220VAC
LiDAR Model	0410-0021	410-LiDAR Measurement Head - 850, 905, 940, 1550 nm bands

SPECIFICATIONS 410-SOLAR, 410-SOLAR-i

410 Solar or 410 Solar-i included in 410 Vis-IR Package.

	410-SOLAR	410-SOLAR-i
MEASURED DATA		
Measured Parameter	Directional hemispherical reflectance (DHR)	
Method	Integrated total reflectance in a band for a given angle of incidence	
Measured Value	Absolute reflectance (0-1), Diffuse Reflectance	Absolute reflectance (0-1)
Calculated Value	Total Solar reflectance, Solar absorptance, specular reflectance	Total Solar reflectance, Solar absorptance
Wavelength Bands (nm)	335-380, 400-540, 480-600, 590-720, 700-1100, 1000-1700, 1700-2500	
ASTM Standards	C1549 E1980 E903	
Angle of Incidence	20° from normal incidence	
Calibration Coupon	Specular, Diffuse	Glazed Ceramic
PERFORMANCE		
Accuracy	+/- .02	
Repeatability	±.005 units	
Beam Spot Size	0.25 inches	0.50 inches
Beam Angle	3° half cone angle	N/A
Measurement Time	10 seconds	7 seconds
Solar Irradiance Functions	Air Mass 0 (AM) Extraterrestrial irradiance (ASTM E490-00) Hazy sky AM1.5 beam-normal irradiance (ASTM E891-87) Clear sky AM1 global horizontal irradiance (SMARTS 2.9.5) Clear sky AM1.5 global irradiance surface tilted 37° (ASTM G173-03) Clear sky AM1.5 global irradiance surface tilted 20° (ASTM G197-14) Clear sky AM1.5 global irradiance surface tilted 90° (ASTM G197-14) Clear sky AM1.5 global horizontal irradiance (SMARTS 2.9.5) Clear sky AM2.0 global horizontal irradiance (SMARTS 2.9.5)	
Sample Size and Geometry	Flat: ≥ 0.5 in. diameter Curved: 6 in. convex; 12 in. concave	
Warm Up Time	90 seconds	
Time Between Measurements	2 seconds	
Sample Temperature	Ambient or heated/cooled to 0 - 100° C	
Operating Temperature	0° to 40° C	
POWER		
Run Time	2 hours on one battery. Battery easily replaced with continuous operation after battery replacement.	
Power Source	Rechargeable battery (standard environmentally friendly NiMH)	
Battery Recharge Time	1 hour	
VIS-NIR Source	Tungsten filament, temperature controlled by user	
DIMENSIONS		
Weight	4.7 lbs. (2.13 kg)	
Form Factor/Size	H 11.54 in., L 9.04 in., W 3.27 in. (29.31 cm x 22.96 cm x 9.44 cm)	
INTERFACE		
Operator Interface	LCD graphics screen, 1/4 VGA, touch screen, software buttons; trigger switch in handle	
Diagnostics	On screen status and signals monitor. Signal values stored with data. Raw data collection and display.	
MISCELLANEOUS		
Format	Data files can be opened and post processed with Excel or a text processor	
Storage	Removable SanDisk (SD) card	
Export control	ECCN #3A999.F	

410 SERIES REFLECTOMETERS & EMISSOMETERS




METHODOLOGY

The basic structure of a measurement head is an internal source, a modified integrating sphere, and detectors. The reflectance measurement is made by collimating the source beam onto the target, the energy is reflected back into the sphere, and eventually detected or dissipated.

The 410 Series Reflectometers measures the integrated surface reflectance of a surface at a given angle of incidence (20° or 60°). The integrating sphere captures the reflected light from the target material, integrating reflections in all directions. Wavelength-filtered detectors measure the total light reflected in each wavelength band and converts it to an analog electrical signal.

The 410 Series Reflectometer electronics processes the detector signals for initial amplification (fixed), filtering, offset adjustment, secondary amplification (variable), and analog to digital conversion. The digitized signals are read by the on-board processor, stored in memory, and then used to determine the target sample reflectance at each incident angle and wavelength band. Those reflectances are used to calculate additional properties such as directional thermal emittance or total hemispherical emittance. Results are displayed on the liquid crystal display touchscreen, and stored on a SecureDigital (SD) card.



INTEGRATING SPHERE SCHEMATIC

Schematic of the integrating sphere in contact with a sample.

Red arrow – illuminating beam
Purple arrow – reflected beam
Green arrows – scattered light

CALIBRATION COUPON



CALIBRATION

An easy calibration process is required before each measurement session. The software GUI will walk the user through the process. Calibration is performed using calibration coupon(s) with known reflectance values.

410 REFLECTOMETERS MODEL COMPARISON GUIDE

The SOC410 Series Reflectometers are portable contact measurement devices designed to take precise, accurate reflectance and emittance measurements. Made with an ergonomic power-drill design, the SOC410 Series lets you easily take measurements in-the-field or around the lab—no cords or external batteries necessary. The world's largest defense, aerospace, and energy companies rely on SOC410 data.



Model	410-Solar	410-Solar-i	410-VIS-IR	ET-100	ET-10	410-DHR
<i>Spectral Bands</i>	335 - 380 nm 400 - 540 nm 480 - 600 nm 590 - 720 nm 700 - 1100 nm 1000 - 1700 nm 1700 - 2500 nm	335 - 380 nm 400 - 540 nm 480 - 600 nm 590 - 720 nm 700 - 1100 nm 1000 - 1700 nm 1700 - 2500 nm	Dual measurement head package consisting of a 410-Solar model and ET100 measurement heads with a single command module	1.5 - 2.0 μm 2.0 - 3.5 μm 3.0 - 4.0 μm 4.0 - 5.0 μm 5.0 - 10.5 μm 10.5 - 21.0 μm	3.0-5.0 μm 8.0-12.0 μm	0.9 - 1.1 μm 1.9 - 2.4 μm 3.0 - 4.0 μm 3.0 - 5.0 μm 4.0 - 5.0 μm 8.0 - 12.0 μm
<i>Calculated Properties</i>	Total, diffuse & specular reflectance absorptance	Total reflectance/absorptance		In-band total reflectance Directional thermal emissivity at 20° Directional thermal emissivity at 60° Hemispherical thermal emissivity	Directional thermal emissivity at 20°	In-band total reflectance In-band emissivity
<i>Angle of Incidence</i>	20°	20°		20° and 60°	20°	20° and 60°
<i>Calibration Coupon(s)</i>	Solar Diffuse Solar Specular	Glazed Ceramic		Specular Gold	Specular Gold	Specular Gold
<i>ASTM Compliance</i>	C1549 E903 E1980	C1549 E903 E1980		E408 E1980		N/A



SURFACE OPTICS
CORPORATION

11555 Rancho Bernardo Road
San Diego, CA 92127

For Information and Ordering

Email: contact@surfaceoptics.com

Phone: +1 858 675-7404

Website: surfaceoptics.com

This information is subject to change without notice.

© Surface Optics Corporation 2021